

CLASSIFICATION 類別		FLOATLESS RELAY 液面控制器	FLOATLESS RELAY 液面控制器	FLOATLESS RELAY 液面控制器	FLOATLESS RELAY 液面控制器
MODEL 型號		AFL-1□	AFL-2□	A61F-G□	A61F-G1□
APPEARANCE 外觀					
DIMENSIONS (mm) 尺寸		114H x 84W x 69.5D	114H x 135W x 69.5D	114H x 84W x 69.5D	114H x 135W x 69.5D
BASE TYPE 底座型號		--	--	--	--
SENSING MODE	GENERAL 一般用	AFL-1	AFL-2	A61F-G	A61F-G1
	HIGH SENSING 高靈敏	AFL-1H	AFL-2H	A61F-GH	A61F-G1H
	LONG DISTANCE 長距離	AFL-1L	AFL-2L	A61F-GL	A61F-G1L
	LOW DENSITY 低感度	AFL-1D	AFL-2D	A61F-GD	A61F-G1D
	TWO LINES 二線式	--	--	--	--
RATED VOLTAGE 額定電壓		AC : 110V / 220V , 110V / 240V , 220V / 380V , 240V / 380V , 50 / 60Hz			
INDICATOR OPERATING 指示燈動作		Two LED's use for two status / 兩只LED燈作狀況指示			
OPERATING VOLTAGE 動作電壓		85 ~ 110% of rated voltage / 額定電壓值的 85 ~ 110%			
SECOND VOLTAGE 電極內電壓		8VAC (except HIGH SENSING 24VAC)			
OPERATE RESISTANCE 動作電阻		4K Ω min. (GENERAL)			
RELEASE RESISTANCE 釋放電阻		15K Ω min. (GENERAL)			
RESPONSE TIME 反應時間		Operate : 80 msec. max. Release : 160 msec. max. / 動作 : 80 msec. 以下, 釋放 : 160 msec. 以下			
CONTACT RATING 接點容量		1C 5A , 250VAC (Resistive load)			
LENGTH OF CABLE 電纜長度		1km max. (GENERAL)			
LIFE	MECHANICAL 機械	5 x 10 ⁶ times min.			
	ELECTRICAL 電氣	10 ⁵ times min.			
SETTING ERROR 設定誤差		100M Ω (DC 500V) min.			
RESET TIME 復歸時間		1500VAC , 50 / 60Hz , for 1 minute			
CONSUMED POWER 消耗功率		3.2VA	6VA	3.2VA	6VA
AMBIENT TEMPERATURE 使用周圍溫度		-10 $^{\circ}$ C ~ +55 $^{\circ}$ C	-10 $^{\circ}$ C ~ +55 $^{\circ}$ C	-10 $^{\circ}$ C ~ +55 $^{\circ}$ C	-10 $^{\circ}$ C ~ +55 $^{\circ}$ C
AMBIENT HUMIDITY 使用周圍濕度		45 ~ 85 % RH	45 ~ 85 % RH	45 ~ 85 % RH	45 ~ 85 % RH
WEIGHT 重量		330g	580g	330g	580g
CONNECTION DIAGRAMS 接線圖		P24-B	P24-C	P24-E	P24-D

