

ANLY TIMER

| MULTI RANGE TIMER 多段式限時繼電器 | | | | FOR - REV RELAY 正逆轉用繼電器 | | VARIABLE FOR - REV RELAY 可調式正逆轉用繼電器 | | TIMER 限時繼電器 | |
|-----------------------------------------------------------------------------------------------------------------|-------|-----------------------------------------------------------------------------------|-------|-----------------------------------------------------------------------------------|--|------------------------------------------------------------------------------------|--------|-------------------------------------------------------------------------------------|--|
| AH2-N□ | | AH2-Y□ | | TWB-N | | TWB-ND | | TRZ | |
|  | |  | |  | |  | |  | |
| 61H x 49W x 70D | | 88H x 58W x 68D | | 61H x 49W x 70D | | 61H x 49W x 70D | | 35H x 35W x 50D | |
| 8PFA | | US-08, P3G-08 | | 8PFA | | 8PFA | | PF083A | |
| A: 1S, 10S, 1M, 10M B: 3S, 30S, 3M, 30M C: 6S, 60S, 6M, 60M D: 1M, 10M, 1H, 10H E: 3M, 30M, 3H, 30H | | | | FOR/REV: 30S fixed, clients' request STOP: 3S fixed, clients' request | | FOR/REV: 30S or 60S variable STOP: 6S variable | | 5 / 10 / 30 / 60 sec. 2 / 3 min. | |
| DC(V): 12, 24 AC(V): 12, 24, 110, 220, 240, 380, 415 440, 50 / 60 Hz | | | | DC(V): 12, 24 AC(V): 12, 24, 110, 220, 240, 380, 415 440, 50 / 60 Hz | | DC(V): 12, 24 AC(V): 12, 24, 110, 220, 240, 50 / 60 Hz | | | |
| Time operating flicker 計時中閃爍指示 | | | | FOR / REV Two indicator lamp FOR / REV 兩只指示燈 | | | | | |
| mode A / B | | mode A / B | | TWB-N | | TWB-NS | TWB-ND | TRZ | |
| 5A | | 5A | | | | | | 5A | |
| 5A | | 5A | | 5A | | 5A | 5A | | |
| 5A | | 5A | | | | | | | |
| 5 x 10 ⁶ times | | | | 5 x 10 ⁶ times | | 5 x 10 ⁶ times | | 5 x 10 ⁵ times | |
| 10 ⁵ times | | | | 10 ⁵ times | | 10 ⁵ times | | 10 ⁵ times | |
| ± 1% max. | | | | ± 1% max. | | ± 1% max. | | ± 3% max. | |
| ± 10% max. | | | | ± 10% max. | | ± 10% max. | | ± 20% max. | |
| ± 1% max. | | | | ± 1.5% max. | | ± 1.5% max. | | ± 5% max. | |
| ± 2% max. | | | | ± 2% max. | | ± 2% max. | | ± 2% max. | |
| 0.1 sec max. | | | | 0.1 sec max. | | 0.1 sec max. | | 0.5 sec max. | |
| 3VA | | | | 2VA | | 2VA | | 2VA | |
| -10 °C ~ +55 °C | | | | -10 °C ~ +55 °C | | -10 °C ~ +55 °C | | -10 °C ~ +55 °C | |
| 45 ~ 85 % RH | | | | 45 ~ 85 % RH | | 45 ~ 85 % RH | | 45 ~ 85 % RH | |
| 220g | | | | 210g | | 230g | | 50g | |
| P19-G | P19-H | P19-G | P19-H | P20-C | | P20-C | | P20-D | |